


DATASHEET

Rockfon Blanka® Activity wall panel



Sounds Beautiful

Rockfon Blanka® Activity wall panel







- Rockfon Blanka Activity wall panels are designed for classrooms and open plan offices where speech intelligibility is crucial and noise and activity levels are very high.
- The smooth, non-directional surface of Rockfon Blanka Activity reduces installation time and the 40mm thickness ensures the highest sound absorption at low frequencies.
- The enhanced surface durability makes it more resistant to dirt and everyday wear and tear, extending the product lifetime.

Product Description

- Stone wool tile
- Visible side: smooth, deep matt, super white painted fleece
- Rear side: back fleece
- Durable painted edges

Application Areas

- Office
- Education
- Retail
- Leisure
- Healthcare

Edge detail	Module size (mm)	Weight (kg/m ²)	Recommended installation System	Recycled content	Cradle to Cradle Certified®	A1-A3 Production stage impact (kg CO ₂ eq/m ²)*	A1-C4 Full life cycle impact (kg CO ₂ eq/m ²)*
 A24	600 x 600 x 40	6.4	Rockfon® System T24 A Wall™	38%		5.51	7.5
	1200 x 600 x 40		Rockfon® System T24 A Wall™				
 B	600 x 600 x 40	6.4	Rockfon® System B Adhesive™	38%		5.51	7.5
	1200 x 600 x 40		Rockfon® System B Adhesive™				
 C	600 x 600 x 40	6.4	Rockfon® System C direct™	38%		5.51	7.5
	1200 x 600 x 40		Rockfon® System C direct™				
	2400 x 600 x 40		Rockfon® System C direct™				

MS = Minimum Suspension


Other dimensions are available on request. Please contact Rockfon.

* For full environmental impact disclosure, see our product EPDs available on rockfon.link/uk-epd. Due to differences in calculation methods and scenario assumptions, environmental impact values are generally not directly comparable between manufacturers.

Performance



Sound absorption
 α_w : 1.00 (Class A)



Edge / Thickness (mm) / Suspension (incl. tile - mm)

Edge / Thickness (mm) / Suspension (incl. tile - mm)	125 Hz	250 Hz	500 Hz	1000 Hz	2000 Hz	4000 Hz	α_w	Absorption class	NRC
40 / 40	0.20	0.70	1.00	1.00	1.00	1.00	1.00	A	1.00



Reaction to fire
 A1



Light reflection and light diffusion
 87% light reflection
 >99% light diffusion



Humidity and sag resistance
 Up to 100% RH



Cleaning
 - Vacuum
 - Damp cloth



Hygiene
 Stone wool provides no sustenance to microorganisms



Surface durability
 Enhanced durability and dirt resistance.
 Class 4



Visual appearance
 Super white surface
 L value: 94.5

The whiteness (L value) of the product is tested in accordance with ISO 7724 and measured on a scale from 1 (black) to 100 (white).

Deep matt surface, perfect in critical side-light
 Gloss: 0.8 gloss unit at 85° angle

The gloss of the product is tested in accordance with ISO 2813.



Recyclability
 Fully recyclable stone wool



Indoor environment
 Rockfon ceiling products are classified in Class E1 in accordance with EN 13964 (EN 717-1).



Material Health
 All materials used in Rockfon products are screened against the list of substances restricted under REACH and do not contain substances of very high concern (SVHC). Rockfon stone wool fibres comply with the safe fibre EU regulation and hold an EUCEB certification.

Sounds Beautiful

